



DISPENSING Microfiltered water

Q1 UNDER EASY

- Room temperature
- Cold

Q1 UNDER BUBBLE

- Room temperature
- Cold
- Cold sparkling

Q1 UNDER BUBBLE R600 - OFFICE USE

- Room temperature
- Cold
- Cold sparkling

Q1 UNDER BUBBLE EVO

- Room temperature
- Cold
- Cold sparkling
- Hot
- Low energy
- Extra silent

BEST SOLUTION FOR

- Home
 - Small Office
 - 1-20 people
-
-

MODELS



White Skinplate

Black Skinplate

Q1 UNDER EASY

Q1UE2A00

Q1UE2B00

Q1 UNDER BUBBLE

Q1UB2A00

Q1UB2B00

Q1 UNDER BUBBLE R600

Q1UB3A00

Q1UB3B00

Q1 UNDER BUBBLE EVO

Q1UB4A00

Q1UB4B00

The EVO version was designed for the home environment, guaranteeing maximum silence, low heat emission and reduced energy consumption.

Q1 UNDER - DATA SHEET



Dimension (mm)	204 (W) x 350 (D) x 420 (H)
Technology	Ice bank
Ice bank	4,3 L capacity
Types of water	Ambient, chilled, sparkling
Test conditions	20°C incoming water and 25°C room temperature
Performance	30 L per hour; 6 L continuously < 12°C
Usage recommendation	Home, Small Office, bar: 1-20 people
Carbonator	Stainless steel carbonator , 0,5 L capacity
Carbonation Pump	Membrane pump
Refrigeration gas	R290
Compressor	1/12 HP - 220/230 V 50 Hz
Thermostat	Mechanical
Condensation	Dynamic ventilation
Coils	6 mm stainless steel
Ø Water Inlet	8 mm
Ø CO2 Inlet	6 mm
Ø Fill Ice bank	8 mm
Water inlet pressure	not over 3 bar - recommended reducer
CO2 inlet pressure	Ideal pressure: in between 3,5 - 4,5 bar
Finish	Housing skinplate, front glass or glazed aluminum
Power Supply	230 V - 50 Hz
Weight	22 Kg
Flow regulator	Included (into the unit)
Filtration	Not included
Water pressure reducers	Not included
CO2 pressure reducers	Not included

SIZE

Millimeters

