



DISPENSING Microfiltered water

Q2 UNDER EASY

- Room temperature
- Cold

Q2 UNDER BUBBLE

- Room temperature
- Cold
- Cold sparkling

BEST SOLUTION FOR

- Small Office
- Bistrot
- 21-50 people



MODELS



White Skinplate



Black Skinplate



Inox

Q2 UNDER EASY

Q2UE2A00

Q2UE2B00

Q2 UNDER BUBBLE

Q2UB2A00

Q2UB2B00

Q2UB2C00

Q2 UNDER - DATA SHEET



Dimension (mm)	353 (W) x 386 (D) x 291 (H)
Technology	Ice bank
Ice bank	7 L capacity
Types of water	Ambient, Cold, Sparkling
Test conditions	20°C incoming water and 25°C room temperature
Performance	40 L per hour, 10 L continuously < 12°C
Usage recommendation	Office and Small Horeca environment: 21-50 people
Carbonator	Stainless steel carbonator, 1 L capacity
Carbonation Pump	Professional membrane pump
Refrigeration gas	R290
Compressor	1/12 HP - 230 V 50 Hz
Thermostat	Mechanical
Condensation	Dynamic ventilation
Coils	6 mm stainless steel
Ø Water Inlet	8 mm
Ø Water Outlet	6 mm
Ø CO2 Inlet	6 mm
Ø Fill Ice bank	8 mm
Water inlet pressure	3 bar recommended
CO2 inlet pressure	Ideal pressure: in between 3,5 - 4,5 bar
Finish	Skinplate / Stainless steel
Power Supply	230 V - 50 Hz
Weight	19,5 kg
Flow regulator	Included (into the unit)
Filtration	Not included
Water pressure reducers	Not included
CO2 pressure reducers	Not included

SIZE

Millimeters

